

DECLARATION OF PERFORMANCE

No. 0764-CPR-0313 – DK – English – vs02

1. *Unique identification code of the product type:*

Rockpanel Premium A2 with visible fixing

2. *Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4):*

Backside print on the board.

3. *Intended use / es*

Internal and external wall and ceiling finishes.

4. *Manufacturer*

ROCKWOOL B.V.
Industrieweg 15
NL-6045 JG Roermond, Netherlands
Tel.: +31 475 353 353

5. *System or systems of AVCP (assessment and verification of constancy of performance of the construction product) as set out in Annex V (amended by: OJ L 157, 27.5.2014, p. 76–79):*

System 1 for reaction to fire and system 2+ for other characteristics

6. *European Assessment Document:*

EAD 090001-00-0404 for Prefabricated compressed mineral wool boards with organic and inorganic finish and with specified fastening system.

European Technical Assessment: ETA-18/0883 of 2025-10-24

Technical Assessment Body

ETA-Danmark A/S
Göteborg Plads 1, DK-2150 Nordhavn, Denmark
Tel.: +45 72 24 59 00
Fax.: +45 72 24 59 04
Internet: www.etadanmark.dk

Notified Body:

Materialprüfanstalt für das Bauwesen
Nienburger Strasse 3, D-30167 Hannover, Germany
Notified Body 0764
Tel.: +49 511 762 3104
Fax.: +49 511 762 4001
Internet: www.mpa-bau.de

and issued:

Certificate of Constancy of performance
No. 0764 – CPR – 0313 of 2025-12-22

7. Characteristics of the product

The Rockpanel Premium A2 panels are surface treated on one side with water-borne primer and a water-borne coloured paint, which has been provided with an extra anti-graffiti clear coat on top of the colour paint. The finishes “Woods”, “Stones” and “Chameleon” contain an (additional) design layer on top of the coloured paint.

The physical properties of ‘Rockpanel Premium A2 are indicated below:

Thickness	11 mm
length, max	3050 mm
width, max	1250 mm
density nominal	1250 kg/m ³
bending strength	length and width $f_{05} \geq 25.5 \text{ N/mm}^2$
Modulus of Elasticity	$\geq 4740 \text{ N/mm}^2$
Thermal conductivity	0.55 W/(m.K)

Clause 8 contains the performances of Rockpanel Premium A2.

8. Declared performance

Table 1 – Euroclass classification of different constructions with Rockpanel Premium A2 boards

Essential characteristics		Basic requirements for construction works BR2 – Safety in case of fire	
Harmonised technical specification		ETA-18/0883 issued on 2025-10-24 EN 13501-1	
Performance			
Fixing method	Set-up	Subframe	Euroclass
Mechanically fixed	Ventilated, with cavity $\geq 20 \text{ mm}$	Vertical aluminium or steel profiles	A2-s1,d0 Open 8 mm joint

Field of application

The following field of application applies.

Euroclass classification

The classification mentioned in Table 1 is valid for the following end use conditions:

Mounting

- Mechanically fixed as described in table 1, to a metal subframe.
- The panels are backed with minimum 50 mm mineral wool insulation with density 30-70 kg/m³ according to EN 13162 with a cavity between the panels and the insulation. See section Insulation below.

Substrates:

- Concrete walls, masonry walls

Insulation:

- Ventilated constructions: The subframe is backed with minimum 50 mm mineral wool insulation with density 30-70 kg/m³ according to EN 13162 with a cavity of minimum 20 mm for between the panels and the insulation.
- Results are also valid for a greater thickness of mineral wool insulation with the same density and the same or better reaction to fire classification.
- The results also apply to panels without insulation, if the substrate chosen according to EN 13238 is made of a panel with Euroclass A1 or A2 (e.g. fibre-cement panels).

Subframe:

- Test results are only valid for an aluminium or steel frame.

Fixings:

- The results are also valid when using smaller mounting distances.
- Test results are also valid for all the mechanical fixings

Cavity:

- Unfilled
- The depth of the cavity is minimum 20 mm.
- Test results are also valid for other higher thicknesses of air space between the back of the board and the insulation.

Joints:

- Vertical joints are without a gasket backing and horizontal joints can be open or closed with an aluminium profile.
- The result from a test with an open horizontal joint is also valid for the same type of panel used in applications with horizontal joints closed by steel or aluminium profiles.
- Max joint width: 8 mm.

The classification is valid for the following product parameters:

Thickness: Nominal 11 mm
Density: Nominal 1250 kg/m³

Table 2 – Performance – Water vapour permeability and water permeability

Essential characteristics		BR3 – Hygiene, Health and environment
Property	Declared values	Harmonised technical specification
Water vapour permeability	NPD – No performance declared	ETA-18/0883 issued on 2025-10-24
Water permeability	NPD – No performance declared	ETA-18/0883 issued on 2025-10-24

Table 3 – Performance – Release of dangerous substances

Essential characteristics		BR3 – Hygiene, Health and environment
Property	Product specification	Harmonised technical specification
Dangerous substances	The kit does not contain/release dangerous substances specified in TR 034, dated April 2013*), except Formaldehyde concentration 0.0105 mg/m ³ . Formaldehyde class E1. The used fibres are not potential carcinogenic No biocides are used in the Rockpanel boards No flame retardant is used in the boards No cadmium is used in the boards.	ETA-18/0883 issued on 2025-10-24

*) In addition to the specific clauses relating to dangerous substances contained in this European technical Assessment, there may be other requirements applicable to the products falling within its scope (e.g. transposed European legislation and national laws, regulations and administrative provisions). In order to meet the provisions of the Construction Products Regulation, these requirements need also to be complied with, when and where they apply.

**Table 4 – Performance – Design value of the axial load for mechanical fixing for Rockpanel Premium A2 boards
Subframe: metal**

Essential characteristics		BR4 – Safety in use			
Harmonised technical specification		ETA-18/0883 issued on 2025-10-24			
For hole diameters fixings see table 5					
Property	11 mm boards	Span in mm [a]		$X_d = X_k / \gamma_M$ in N [c] Middle / Edge/ Corner	Table in ETA
		a fixing	b board		
Design value of the axial load $X_d = X_k / \gamma_M$	Rivet fixing [b]	750	750	614 / 394 / 398	12

[a] See Table 6a and 6b

[b] For specifications fixings see Table 8

[c] The following material factors have been used for the Premium A2: $\gamma_M = 2.0$; $\gamma_m = 1.6$; for the connection rivet-subframe $\gamma_M = 1.25$

Table 5 – Performance mechanical fixings – Hole diameters for Rockpanel Premium A2 boards

Essential characteristics	BR4 – Safety in use			
Harmonised technical specification	ETA-18/0883 issued on 2025-10-24			
Fixing type [a]	Fixed hole	Moving hole	Slotted hole	Board dimension considered
Rivet	5.1	8.0	5.1 * 8.0	1200 * 3050

[a] For specifications fixings see Table 8; for installation methods see Table 6a and 6b

Table 6a – Performance fixings according to table 4 and 5 with the required edge distances, maximum distances and horizontal installation of boards.

Essential characteristics	BR4 – Safety in use				
Harmonised technical specification	ETA-18/0883 issued on 2025-10-24 Table 10, 11, 12 and fig. 2				
<p>The diagrams illustrate the placement of different fixing types on a board. The first diagram shows 'Slotted holes' (SP) and 'Fixed points' (FP) with dimensions l_m and l_{mv} and edge distance a_1. The second diagram shows 'Fixed points' (FP) and 'Fixed points with sleeves' (FPM) with dimensions l_b and b_2. The third diagram shows corner (C), edge (E), and middle (M) positions with dimensions a, a_1, and b.</p>	FP/SP [b]	'Fixed hole' FP and 'slotted holes' SP (according to table 5) in the middle of the vertical part of the board All the other fixings points are 'moving points'			
	l_m	Length max 3050 mm			
	l_{mv}	'moving length' \leq 1510 mm			
	l_b	Length of the board			
	b_2	Max. 750 mm; b_2 in the central area of the board length l_b			
	FPM [b]	Creating a fixed point by the use of a sleeve FPM			
	Location of the fastener: M: Middle of the board E: Edge of the board C: Corner of the board				
	Fixing type	b_{max}	a_{max}	a_1	a_2
	Rivet [a]	750	750	\geq 20	\geq 50
	Use of sleeves for Rivet fixing		Drill hole according to Table 5	Sleeve	
Subframe Aluminium	FPM – Sleeve [a] [b]	8 mm	$\varnothing 8 \times 7,5$ – drill hole $\varnothing 5.1$		
	FP – 'Fixed point' FP (according to Table 5) in central area of the vertical edge of the board.				

[a]: For correct fixing (SP, FP and SPM) a riveting tool with rivet spacer must be used (e.g. 0.3 mm).

[b]: Subframe aluminium

Table 6b – Performance fixings according to table 4 and 5 with the required edge distances, maximum distances and vertical installation of boards.

<i>Essential characteristics</i>		BR4 – Safety in use	
<i>Harmonised technical specification</i>		ETA-18/0883 issued on 2025-10-24 Table 10, 11, 12 and fig. 2	
		FP/SP [b]	'Fixed points' FP and 'slotted points' SP (according to Table 5) in the middle of the vertical part of the board
		FPM [b]	Fixed point realized by a sleeve FPM
		SPM [b]	Slotted hole realized by a side sleeve
All the other fixing points are 'moving' points.			
		l_b	Length of the board
		l_{b2}	Ca $l_b / 2$
		b_3	max. 400 mm
		b_4	max. 600 mm
		<i>Drill hole according to Table 5</i>	<i>Sleeve</i>
Subframe	FPM – Sleeve [a] [b]	8 mm	Ø8 x 7,5 – hole Ø5.1
Aluminium	SPM – Side sleeve [a][b]	8 mm	Ø8 x 7,5 – hole Ø5.1 x 6.2

[a]: For correct fixing (SP, FP and SPM) a riveting tool with rivet spacer must be used (e.g. 0.3 mm).

[b]: Subframe aluminium

Table 7 – Performance shear strength mechanical fixings

<i>Essential characteristics</i>		BR4 – Safety in use		
<i>Harmonised technical specification</i>		ETA-18/0883 issued on 2025-10-24		
		<i>Fixing</i>	<i>Failure load</i>	<i>Deformation</i>
Characteristic shear strength mechanical fixings		Rivets	2194 N	4.4 mm
Average values				

Table 8 – Specifications mechanical fixings – Rivet aluminium or stainless steel [e]

Harmonised technical specification		ETA-18/0883 issued on 2025-10-24 – Tabel 5			
		SFS Aluminium [d]	SFS Stainless steel A4 [a]	MBE Aluminium [d]	MBE Stainless steel [b]
	Code	AP14-50210-S	SSO-D15-50180	FN-AI5-5x21 K14	FN-A4-5x18 K15
	Body	Aluminium EN AW-5019 (AlMg5) in accordance with EN 755-2	Stainless steel material number 1.4578 in accordance with EN 10088	Aluminium EN AW-5019 (AlMg5) in accordance with EN 755-2	Stainless steel material number 1.4578 in accordance with EN 10088
	Mandrel	Stainless steel material number 1.4541 in accordance with EN 10088	Stainless steel material number 1.4541 in accordance with EN 10088	Stainless steel material number 1.4541 in accordance with EN 10088	Stainless steel material number 1.4541 in accordance with EN 10088
	Pull-out strength	$F_{u,5} = 1882 \text{ N}$	$F_{u,5} = 1339 \text{ N}$	$F_{u,5} = 1882 \text{ N}$	$F_{u,5} = 1339 \text{ N}$
	d ¹	5	5	5	5
	d ²	14	15	14	15
	d ³	2.7	3.25	2.7	3.25
	L	21	18	21	18
	k	1.5	1.5	1.5	1.5
	Profile	Aluminium t ≥ 1.5 mm	Steel t ≥ 1.0 mm	Aluminium t ≥ 1.5 mm	Steel t ≥ 1.0 mm

[a]: The minimum thickness of the vertical steel profiles is 1.0 mm. The steel quality is S320GD +Z EN 10346 number 1.0250 (or equivalent for cold forming). For minimum coating thickness see [c].

[b]: The minimum thickness of the vertical steel profiles is 1.5 mm. The steel quality is EN 10025-2:2004 S235JR number 1.0038. For minimum coating thickness see [c].

[c]: The minimum coating thickness (Z or ZA) is determined by the corrosion rate (amount of corrosion loss in thickness per year) which depends on the specific outdoor atmospheric environment. The International Zinc association can be consulted for more information.

The coating designation (classification which determines the coating mass) shall be agreed between the contractor and the building owner. Alternatively a hot dip galvanized coating according to EN ISO 1461 can be used.

[d]: The aluminium is minimum AW-6060 according EN 755-2. The $R_m/R_{p0,2}$ value is ≥ 170/140 for profile T6 and ≥ 195/150 for profile T66.

[e]: For correct fixing a riveting tool with rivet spacer must be used (e.g. 0.3 mm)

Table 9 – Performance Impact resistance

Essential characteristics	BR4 – Safety in use		
Harmonised technical specification	ETA-18/0883 issued on 2025-10-24		
Impactor	Category	Table in ETA	
Hard body [1 J]	IV	6	
Hard body [3 J]	III, II and I		
Hard body [10 J]	II and I		
Soft body [10 J]	IV and III		

Table 10 – Performance dimensional stability

Essential characteristics	BR4 – Safety in use		
Harmonised technical specification	ETA-18/0883 issued on 2025-10-24		
	Length	Width	Table in ETA
Cumulative dimensional change [a]	0.061 %	0.064 %	7
Dry heat 23°C / 50% to 23°C / 0% (mm/m)	-0.240	-0.290	
Coefficient of thermal expansion (10^{-6} K^{-1})	9.7	9.7	
Coefficient of moisture expansion 42% RH difference after 4 days (mm/m)	0.204	0.207	

[a]: As a consequence the minimum joint width shall be 3 mm, preferably 5 mm.

Table 11 – Resistance to hygro-thermal cycles and Xenon Arc exposure

<i>Essential characteristics</i>	Aspects of durability and serviceability	
<i>Harmonised technical specification</i>	ETA-18/0883 issued on 2025-10-24	
Resistance to Hygrothermal cycles		<i>Performance</i>
Resistance to Xenon Arc exposure <i>EOTA TR010 climate class S (Technical Report 010)</i> 5000 hours artificial weathering	Finish 'ProtectPlus'	Pass ISO 105 A02: 4 or better


9. The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf
of the manufacturer by:

ROCKWOOL B.V.
Edwin De Wolf
Managing Director

At: Roermond,
The Netherlands

on: 09-03-2026



DOP in accordance with Commission Delegated Regulation (EU) No 574/2014 of 21 February 2014 amending Annex III to Regulation (EU) No 305/2011 of the European Parliament and of the Council on the model to be used for drawing up a declaration of performance on construction products, <http://eur-lex.europa.eu/legal-content/EN/TXT/?uri=celex%3A32014R0574>, OJ L 159, 28.5.2014, p. 41–46